



Declaration of performance according to Regulation (EU) 305/2011

No. W105/47F

1.	Unique identification code of the product-type	Kalfire W105/47F	Kalfire W105/47F	
2.	Intended use	Fireplace inserts for solid fue	Fireplace inserts for solid fuels	
3.	Trade mark	Kal-fire B.V. Geloërveldweg 21 5951 DH Belfeld Nederland	www.kalfire.com	
4.	System or systems of assessment and verification of consta Annex V: System 3	of constancy of performance of the construction product as set out in		
5.	The notified laboratory performed of the product type on the basis of type testing under system 3			
	Notified body	Fraunhofer Institut, Nobelst Stuttgart, Deutschland	Fraunhofer Institut, Nobelstraße 12, D-70569 Stuttgart, Deutschland	
	Notified body no.	1004	1004	
	Test report no.	P8-019-2015	P8-019-2015	
6.	Harmonized technical spezification	EN 13229:2001/A2:2004/AC	EN 13229:2001/A2:2004/AC:2007	
	Essential characteristics	Performance	Performance	
	Fire safety	pass	pass	
	Flue gas temperature at nominal heat output	245°C	245°C	
	Safety distance to combustible material	Minimum distances in mm	Minimum distances in mm	
		rear =	150 mm	
		side =	150 mm	
		front =	150 mm	
		floor =	0 mm	
	Risk of burning fuelfalling out	pass	pass	
	cleanability	pass	pass	
	Emission of combustion products	≤ 0,1%	≤ 0,1%	
	Surface temperature	pass	pass	
	Electrical safety	pass	pass	
	Release of dangerous substance	no value determined	no value determined	
	Max. operation pressure	not applicable	not applicable	
	Mechanical resistance (to carry a a chimney/flue)	pass	pass	
	Thermal output			
	Nominal heat output	17,6 kW	17,6 kW	
	Room heating output	not applicable	not applicable	
	Water heating output	not applicable	not applicable	
	Efficiency	≥80%	≥80%	

Signed on behalf of the manufacturer

 $\label{thm:continuous} {\sf Drs\,Ing\,Beijko\,van\,Melick\,Msc,Managing\,Director\,-\,Kal-fire\,B.V.}$

name and function

Belfeld, 08-10-2018

place and date of issue

signature