Technical data sheet
BANDO

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Wood storage panel	
Without wood storage panel	✓
Coating	
Black	✓
Platinum	✓
Mocha	✓
Cladding	
Soapstone	✓
Natural stone porto	✓
Air control	
Manual	✓
Rotating console	
Rotating console	✓ With a rotating console, smoke outlet is only possible upwards.



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
BANDO

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	222 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Top	✓
Rear	✓
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
European standard	EN 16510
MINERGIE® compatible	✓
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	3 Stelle

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
BANDO

SERVICES

Thermal output	
Nominal heat output	6.3 kW
Fuelwood requirement	1.9 ≈ kg/h
Energy efficiency	≥75 %
Combustion air requirement	18.1 m^3/h
Triple values	
Exhaust gas mass flow	6.3 g/s
Exhaust temperature	319 °C
Minimum flue draught	-12 Pa
Fire safety	
Dust at 13 % O2	≤40 mg/Nm^3
CO emission at 13 % O2	≤0.12 %
CO emission at 13 % O2	≤1500 mg/Nm^3
OGC at 13 % O2	≤120 mg/Nm^3
NOx at 13 % O2	≤200 mg/Nm^3

Safety distances:

Information on safety distances can be found in the installation manual.

Note:

Please observe the national/regional regulations for floor protection.

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch