

# Technical data sheet

## NEXO 185 GAS

### OPTIONS

| Firebox door                 |             |
|------------------------------|-------------|
| Steel door                   | ✓           |
| Glass door                   | ✓           |
| Side window                  |             |
| Without side window          | ✓           |
| Two side windows             | ✓           |
| One side window (left/right) | ✓           |
| Coating                      |             |
| Black                        | ✓           |
| Platinum                     | ✓           |
| Mocha                        | ✓           |
| Nickel                       | ✓           |
| Sand                         | ✓           |
| White                        | ✓           |
| Top plates                   |             |
| Steel 8 mm                   | ✓           |
| Stainless steel              | ✓           |
| Soapstone                    | ✓           |
| Heat-storage module©         |             |
| Heat-storage module©         | 100   75 kg |



# Technical data sheet

## NEXO 185 GAS

| Side bench        |          |
|-------------------|----------|
| Side bench narrow | ✓        |
| Side bench wide   | ✓        |
| Operating         |          |
| Remote control    | Standard |
| attika fire app   | Option   |
| Home Automation   | Option   |

# Technical data sheet

## NEXO 185 GAS

### PRODUCT INFORMATION

| Connections                         |                       |
|-------------------------------------|-----------------------|
| Flue pipe Ø (LAS)                   | 100/150 mm            |
| Gas connection                      | Ø 12 mm   1/2"   3/8" |
| Flue pipe outlet                    |                       |
| Top                                 | ✓                     |
| Rear                                | ✓                     |
| Side                                | ✓                     |
| Weight depending on model/equipment |                       |
| Weight depending on model/equipment | 125 - 190 kg          |
| Permissible chimney systems         |                       |
| Schiedel Ontop Metaloterm           | ✓                     |
| Jeremias                            | ✓                     |
| M&G Group                           | ✓                     |
| Poujoulat                           | ✓                     |
| Certifications                      |                       |
| Energy efficiency class             | A                     |
| CE                                  | EU 2016/426           |
| SVGW                                | 18-035-3              |

# Technical data sheet

## NEXO 185 GAS

### SERVICES

| Output range                               |                        |
|--|------------------------|
| Natural gas   G20/20 mbar                  | 1.2-6.4 kW             |
| Propane gas   G31/50 mbar                  | 1.3-5.8 kW             |
| Gas consumption                            |                        |
| Natural gas   G20/20 mbar                  | 0.84 m <sup>3</sup> /h |
| Propane gas   G31/50 mbar                  | 0.29 m <sup>3</sup> /h |
| Maximum load                               |                        |
| Natural gas   G20/20 mbar                  | 9.1 kW                 |
| Propane gas   G31/50 mbar                  | 8 kW                   |
| Energy efficiency                          |                        |
| Efficiency class Natural gas   G20/20 mbar | 2                      |
| Efficiency class Propane gas   G31/50 mbar | 2                      |

# Technical data sheet

## NEXO 185 GAS

### INSTALLATION

| Distances to combustible materials (without side window) |         |
|--|---------|
| A: to the back   | 50 mm   |
| B: to the side wall                                      | 250 mm  |
| C: to the front  | 700 mm  |
| D: upwards   | 1000 mm |
| Distances to combustible materials (with side window)    |         |
| A: to the back   | 50 mm   |
| B: to the side wall                                      | 300 mm  |
| C: to the front  | 700 mm  |
| D: upwards   | 1000 mm |

# Technical data sheet

## NEXO 185 GAS

### Sketches of safety distances

