

Technical data sheet

PILAR

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Coating	
Black	✓
Platinum	✓
Mocha	✓
Nickel	✓
Sand	✓
White	✓
Handles	
Oak wood black	✓
«classic»	✓
Stainless steel	✓
Corian [®]	✓
Calf leather brown	✓
Calf leather black	✓
Oak nature	✓



Technical data sheet

PILAR

Top plates	
Steel 8 mm	✓
Stainless steel with convection regulator	✓
Soapstone	✓
Step	✓
Stainless steel ring for step	✓
Heat-storage module©	
Heat-storage module©	120 60 kg
Air control	
CleverAIR™	✓
ElectronicAIR™	✓
Manual	✓
Air-system	
Air-system	✓
Rotating console	
Rotating console	✓ With a rotating console, smoke outlet is only possible upwards.

Technical data sheet

PILAR

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	170 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Top	✓
Rear	✓
Certifications	
Energy efficiency class	A+
Multiple occupancy	✓
Eco Design	✓
EN NORM	EN 13240
MINERGIE® compatible	✓
DIBt	Z-43.12-476
BImSchV	Stufe 2
Flamme Verte	7*
Classe energetica di appartenenza	3 Stelle

Technical data sheet

PILAR

SERVICES

Thermal output	
Nominal heat output	4.5 kW
Thermal output range min./max.	2-9 kW
Fuelwood requirement	1.6 ≈ kg/h
Energy efficiency	81 %
Combustion air requirement	12.6 m ³ /h
Triple values	
Exhaust gas mass flow	4.4 g/s
Exhaust temperature	254 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O ₂	12 mg/Nm ³
CO emission at 13 % O ₂	0.074 %
CO emission at 13 % O ₂	927 mg/Nm ³
CO ₂ concentration	10.2 %
OGC at 13 % O ₂	82 mg/Nm ³
NO _x at 13 % O ₂	73 mg/Nm ³

Technical data sheet

PILAR

INSTALLATION

Distances to combustible materials (without side window)	
A: to the back	100* mm
B: to the side wall	500 mm
C: to the front	850 mm
D: upwards	750 mm

Note

Please observe the national/regional regulations for floor protection.

*See installation manual

Technical data sheet

PILAR

Sketches of safety distances

