

Technical data sheet

Q-BE

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Coating	
Black	✓
Platinum	✓
Mocha	✓
Nickel	✓
Sand	✓
White	✓
Handles	
Oak wood black	✓
Stainless steel	✓
Corian [®]	✓
Calf leather brown	✓
Calf leather black	✓
Oak nature	✓
Heat-storage module [©]	
Heat-storage module [©]	25 kg
Air control	
CleverAIR [™]	✓



Technical data sheet

Q-BE

Air-system	
Air-system	✓
Side bench	
Side bench narrow	✓
Side bench wide	✓

Note

The Q-BE combustion chamber can be rotated as standard.

Technical data sheet

Q-BE

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	125 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Top	✓
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
EN NORM	EN 13240
MINERGIE® compatible	✓
DIBt	Z-43.12.403
BImSchV	Stufe 2
Flamme Verte	7*
Classe energetica di appartenenza	4 Stelle

Technical data sheet

Q-BE

SERVICES

Thermal output	
Nominal heat output	5.9 kW
Thermal output range min./max.	4-8 kW
Fuelwood requirement	2 ≈ kg/h
Energy efficiency	80 %
Combustion air requirement	15.5 m ³ /h
Triple values	
Exhaust gas mass flow	5.1 g/s
Exhaust temperature	300 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O ₂	16 mg/Nm ³
CO emission at 13 % O ₂	0.069 %
CO emission at 13 % O ₂	862 mg/Nm ³
CO ₂ concentration	11.3 %
OGC at 13 % O ₂	55 mg/Nm ³
NO _x at 13 % O ₂	53 mg/Nm ³

Technical data sheet

Q-BE

INSTALLATION

Distances to combustible materials (without side window)	
A: to the back	200 mm
B: to the side wall	200 mm
C: to the front	750 mm
D: upwards	500 mm
Distances to combustible materials (with side window)	
A: to the back	200 mm
B: to the side wall	750 mm
C: to the front	750 mm
D: upwards	500 mm

Note

Please observe the national/regional regulations for floor protection.

Technical data sheet

Q-BE

Sketches of safety distances

