

Technical data sheet

Q-TEE 2 C soapstone

OPTIONS

Firebox door	
Steel door	✓
Glass door	✓
Wood storage panel	
Without wood storage panel	✓
With wood storage panel	✓
Coating	
Black	✓
Cladding	
Soapstone	✓
Natural stone «porto»	✓
Handles	
Oak wood black	✓
«classic»	✓
Stainless steel	✓
Calf leather brown	✓
Calf leather black	✓
Air control	
Manual	✓
Air-system	
Air-system	✓



Technical data sheet

Q-TEE 2 C soapstone

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	356 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Top	✓
Rear	✓
Certifications	
Energy efficiency class	A+
Multiple occupancy	✓
Eco Design	✓
EN NORM	EN 13240
MINERGIE® compatible	✓
BImSchV	Stufe 2
Flamme Verte	7*
Classe energetica di appartenenza	4 Stelle

Technical data sheet

Q-TEE 2 C soapstone

SERVICES

Thermal output	
Nominal heat output	6.5 kW
Thermal output range min./max.	3-8 kW
Fuelwood requirement	1.8 ≈ kg/h
Energy efficiency	81 %
Combustion air requirement	15.5 m ³ /h
Triple values	
Exhaust gas mass flow	5.2 g/s
Exhaust temperature	263 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O ₂	14 mg/Nm ³
CO emission at 13 % O ₂	0.08 %
CO emission at 13 % O ₂	989 mg/Nm ³
CO ₂ concentration	10.4 %
OGC at 13 % O ₂	63 mg/Nm ³
NO _x at 13 % O ₂	90 mg/Nm ³

Technical data sheet

Q-TEE 2 C soapstone

INSTALLATION

Distances to combustible materials (without side window)	
A: to the back	300 mm
B: to the side wall	400 mm
C: to the front	1200 mm
D: upwards	800 mm

Note

Please observe the national/regional regulations for floor protection.

Technical data sheet

Q-TEE 2 C soapstone

Sketches of safety distances

