

Technical data sheet

VISIO 3:1 UNIQ

OPTIONS

Support frame	
Black, 6mm	✓
Stainless steel, 6mm	✓
Window frame	
Black	✓
Stainless steel	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
Air-system	
Air-system	✓



Technical data sheet

VISIO 3:1 UNIQ

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	285 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
EN NORM	EN 13229
BImSchV	Stufe 2
Flamme Verte	7*
Classe energetica di appartenenza	3 Stelle

Technical data sheet

VISIO 3:1 UNIQ

SERVICES

Thermal output	
Nominal heat output	11.3 kW
Fuelwood requirement	3.5 ≈ kg/h
Energy efficiency	≥75 %
Combustion air requirement	37.5 m ³ /h
Triple values	
Exhaust gas mass flow	12.3 g/s
Exhaust temperature	262 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O ₂	≤40 mg/Nm ³
CO emission at 13 % O ₂	≤0.12 %
CO emission at 13 % O ₂	≤1500 mg/Nm ³
CO ₂ concentration	8.1 %
OGC at 13 % O ₂	≤120 mg/Nm ³
NO _x at 13 % O ₂	≤200 mg/Nm ³

Technical data sheet

VISIO 3:1 UNIQ

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	800 mm
Furniture distance from the side glass	
B: Furniture distance from the side glass	600 mm

CONVECTION AIR

Convection air above	min. 700 cm ²
Convection air below	min. 500 cm ²

Note

Maximum weight supported by the frame: 200 kg.

Technical data sheet

VISIO 3:1 UNIQ

Installation

