

# Technical data sheet

## VISIO 3:1 UNIQ

### OPTIONS

Support frame	
Black, 6mm	✓
Window frame	
Black	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
Air-system	
for room air independent installation	✓



# Technical data sheet

## VISIO 3:1 UNIQ

### PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	285 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
European standard	EN 16510
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	3 Stelle

# Technical data sheet

## VISIO 3:1 UNIQ

### SERVICES

Thermal output	
Nominal heat output	11.3 kW
Fuelwood requirement	3.5 ≈ kg/h
Energy efficiency	≥75 %
Combustion air requirement	37.5 m <sup>3</sup> /h
Triple values	
Exhaust gas mass flow	12.6 g/s
Exhaust temperature	324 °C
Minimum flue draught	-12 Pa
Fire safety	
Dust at 13 % O <sub>2</sub>	≤40 mg/Nm <sup>3</sup>
CO emission at 13 % O <sub>2</sub>	≤0.12 %
CO emission at 13 % O <sub>2</sub>	≤1500 mg/Nm <sup>3</sup>
OGC at 13 % O <sub>2</sub>	≤120 mg/Nm <sup>3</sup>
NO <sub>x</sub> at 13 % O <sub>2</sub>	≤200 mg/Nm <sup>3</sup>

#### Safety distances:

Information on safety distances can be found in the installation manual.

#### Note:

Maximum weight supported by the frame: 200 kg.