

# Technical data sheet

## VISIO 90 RD

### OPTIONS

|                              |          |
|------------------------------|----------|
| Designframe (non supporting) |          |
| Black                        | ✓        |
| Stainless steel              | ✓        |
| Anti-reflective glass        |          |
| Anti-reflective glass        | ✓        |
| Operating                    |          |
| Remote control               | Standard |
| attika fire app              | Option   |
| Home Automation              | Option   |



# Technical data sheet

## VISIO 90 RD

### PRODUCT INFORMATION

| Connections                         |                       |
|-------------------------------------|-----------------------|
| Flue pipe Ø (LAS)                   | 130/200 mm            |
| Gas connection                      | Ø 12 mm   1/2"   3/8" |
| Weight depending on model/equipment |                       |
| Weight depending on model/equipment | 125 - 150 kg          |
| Permissible chimney systems         |                       |
| Schiedel Ontop Metaloterm           | ✓                     |
| Jeremias                            | ✓                     |
| M&G Group                           | ✓                     |
| Poujoulat                           | ✓                     |
| Certifications                      |                       |
| Energy efficiency class             | A                     |
| CE                                  | EU 2016/426           |
| SVGW                                | 19-015-3              |

# Technical data sheet

## VISIO 90 RD

### SERVICES

| Output range                               |                       |
|--|-----------------------|
| Natural gas   G20/20 mbar                  | 1.1-6.5 kW            |
| Propane gas   G31/50 mbar                  | 1.8-8.9 kW            |
| Gas consumption                            |                       |
| Natural gas   G20/20 mbar                  | 0.9 m <sup>3</sup> /h |
| Propane gas   G31/50 mbar                  | 0.4 m <sup>3</sup> /h |
| Maximum load                               |                       |
| Natural gas   G20/20 mbar                  | 8.1 kW                |
| Propane gas   G31/50 mbar                  | 11.2 kW               |
| Energy efficiency                          |                       |
| Efficiency class Natural gas   G20/20 mbar | 1                     |
| Efficiency class Propane gas   G31/50 mbar | 1                     |

### INSTALLATION

| Furniture distance from the front glass    |        |
|--|--------|
| A: Furniture distance from the front glass | 500 mm |
| Furniture distance from the side glass     |        |
| B: Furniture distance from the side glass  | 500 mm |

### CONVECTION AIR

|                      |                     |
|----------------------|---------------------|
| Convection air above | 200 cm <sup>2</sup> |
| Convection air below | 200 cm <sup>2</sup> |

# Technical data sheet

## VISIO 90 RD

### Installation

