Technical data sheet
VISIO TUNNEL

OPTIONS

Support frame	
Black, 6mm	✓
Window frame	
Black	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
Air-system	
for room air independent installation	✓



ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
VISIO TUNNEL

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	235 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A
Eco Design	✓
European standard	EN 16510
BImSchV	Stufe 2
Flamme Verte	✓
Classe energetica di appartenenza	4 Stelle

One side has a lifting door, the other side is fixed. Both can be tilted for cleaning.

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch

Technical data sheet
VISIO TUNNEL

SERVICES

Thermal output	
Nominal heat output	8.6 kW
Fuelwood requirement	2.5 ≈ kg/h
Energy efficiency	≥75 %
Combustion air requirement	23.5 m^3/h
Triple values	
Exhaust gas mass flow	8.1 g/s
Exhaust temperature	316 °C
Minimum flue draught	-12 Pa
Fire safety	
Dust at 13 % O2	≤40 mg/Nm^3
CO emission at 13 % O2	≤0.12 %
CO emission at 13 % O2	≤1500 mg/Nm^3
OGC at 13 % O2	≤120 mg/Nm^3
NOx at 13 % O2	≤200 mg/Nm^3

Safety distances:

Information on safety distances can be found in the installation manual.

Note:

Maximum weight supported by the frame: 200 kg.

ATTIKA FEUER AG I Brunnmatt 16 I CH-6330 Cham I Tel. +41 41 784 80 80 I info@attika.ch I www.attika.ch