

Technical data sheet

VIVA L oven

OPTIONS

Firebox door	
Steel door	✓
Side window	
Without side window	✓
Coating	
Black	✓
Platinum	✓
Mocha	✓
Nickel	✓
Sand	✓
White	✓
Handles	
Oak wood black	✓
«classic»	✓
Stainless steel	✓
Corian [®]	✓
Calf leather brown	✓
Calf leather black	✓
Oak nature	✓
Top plates	
Steel 8 mm	✓



Technical data sheet

VIVA L oven

Air control	
Manual	✓
Air-system	
Air-system	✓

Technical data sheet

VIVA L oven

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	140 kg
Ø Smoke outlet	
Ø Smoke outlet	150 mm
Ø Air inlet	
Ø Air inlet	100 mm
Flue pipe outlet	
Rear	✓
Certifications	
Energy efficiency class	A
Multiple occupancy	✓
Eco Design	✓
EN NORM	EN 13240
MINERGIE® compatible	✓
DIBt	Z-43.12-425
BImSchV	Stufe 2
Flamme Verte	7*
Classe energetica di appartenenza	4 Stelle

Technical data sheet

VIVA L oven

SERVICES

Thermal output	
Nominal heat output	5.6 kW
Thermal output range min./max.	3-7 kW
Fuelwood requirement	1.8 ≈ kg/h
Energy efficiency	80 %
Combustion air requirement	13 m ³ /h
Triple values	
Exhaust gas mass flow	4.4 g/s
Exhaust temperature	282 °C
Required delivery pressure	12 Pa
Required delivery pressure at 0.8 times the nominal heat output	10 Pa
Fire safety	
Dust at 13 % O ₂	6 mg/Nm ³
CO emission at 13 % O ₂	0.0602 %
CO emission at 13 % O ₂	752 mg/Nm ³
CO ₂ concentration	10.9 %
OGC at 13 % O ₂	43 mg/Nm ³
NO _x at 13 % O ₂	80 mg/Nm ³

Technical data sheet

VIVA L oven

INSTALLATION

Distances to combustible materials (without side window)	
A: to the back	75 mm
B: to the side wall	400 mm
C: to the front	850 mm
D: upwards	450 mm

Note

Please observe the national/regional regulations for floor protection.

Technical data sheet

VIVA L oven

Sketches of safety distances

