

EU DECLARATION OF PERFORMANCE

Regulation (EU) 305/2011 No. 0001 – CRP-2013/07/01



No.: 124

- | | |
|--|---|
| 1. Unique identification code of the product-type | Rais: Visio 1, Visio 2, Visio 3 (All variants)
Attika: Visio 1, Visio 2, Visio 3 (All variants) |
| 2. Type | Room heater burning solid fuel without hot water supply |
| 3. Intended use | Domestic room heater |
| 4. Manufacturer | Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, Germany www.spartherm.com |
| 5. Authorised representative | RAIS A/S, Industrivej 20, Vangen, DK-9900 Frederikshavn, Denmark, www.rais.com / www.attika.ch
Phone number: +45 98 47 90 33, Webmail: kundeservice@rais.dk |
| 6. System of assessment AVCP | System 3 |
| 7. Approved Body | Danish Technological Institute - Identification no. 1235
Teknologiparken, Kongsvang Allé 29, DK-8000 Århus C, Danmark
a. 300-ELAB-2080-EN |
| 8. Declared performance | Harmonized technical specification: EN 16510-2-2:2022 |

Essential characteristics				Performance		
Fire safety				Visio 1	Visio 2	Visio 3
Reaktion ved brand		A1		Front model	Corner model	Three-sided model
Distance to combustible materials Minimum distances [mm] <i>For other installation or wall settings see installation guide</i>	d _R	To back wall from back of installation box		0 mm	0 mm	0 mm
	d _S	To side wall		400 mm	300 mm *850 mm	750 mm
	d _C	From top convection opening to ceiling		200 mm	200 mm	200 mm
	d _F	Front/front of oven		1400 mm	1200 mm	1200 mm
	d _B	From bottom edge of door to floor		385 mm	385 mm	385 mm
				Insulated flue pipe (Distances measured on the outside of the installation box). *Distance to side wall / furniture from side glass		
				Visio 1, 2, 3		
Risk of burning fuel falling out				Pass		
OGC (13 % O ₂)				≤ 120	mg/Nm ³	
CO-emission of combustion products (13 % O ₂)				≤ 0,12	%	
				≤ 1500	mg/Nm ³	
NO _x (13 % O ₂)				≤ 200	mg/Nm ³	
Dust (13 % O ₂)				< 40	mg/Nm ³	
Surface temperature				Pass		
Electrical safety				NPD		
Cleanability				Pass		
Flue gas temperature at nominal heat output		T _s	299	°C		
Minimum flue draught		p	-12	Pa		
Flue gas mass flow		ϕ _{f,g}	7,9	g/s		
Chimney designation		T _{class}	T400 G			
Thermal output						
Nominal heat output		P	7,9	kW		
Room heating output		P _{SH}	7,9	kW		
Energy efficiency		η	≥ 75	%		
Seasonal efficiency		η _s	≥ 65	%		
Energy efficiency index		EEI	106 - A			
Environmental sustainability		ESI	NPD			

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D / Quality Manager

Place FREDERIKSHAVN, DENMARK

Date 31-07-2025


 Signature