

DECLARATION OF PERFORMANCE

Regulation (EU) 305/2011 No. 0001 — CPR-2013/07/01

No.: 124 Elements

- | | | | |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| 1. Unique identification code of the product-type | RAIS VISIO 3 Elements, ATTIKA VISIO 3 Elements | | |
| 2. Type | Inset appliance burning solid fuel without hot water supply | | |
| 3. Intended use | Domestic room heater | | |
| 4. Manufacturer | Attika Feuer AG
Brunmatt 16, CH-6330 Cham | Telephone +41 (0)41 784 80 80
Telefax +41 (0)41 784 80 84
Webmail info@attika.ch
Homepage www.attika.ch | |
| 5. Authorised representative | n/a | | |
| 6. System of assessment AVCP | System 3
The notified laboratory <i>Rhein-Ruhr Feuerstätten Prüfstelle - Identification no. 1625 Im Lipperfeld 34 b, 46047 Oberhausen</i> | | |
| 7. Notified body | performed the determination of the product type on the basis of type testing under system 3 and issued test report
a. RRF-40 17 4624 | | |
| 8. Declared performance | Harmonized technical specification: | EN 13229:2001/A2:2004/AC:2007 | |

Essential characteristics		Performance
Fire safety		<ul style="list-style-type: none"> • Insulated flue 30mm concrete elements Distances are measured externally on the built-in box
Reaction to fire	A1	Visio 3 Elements
Distance to combustible materials Minimum distances [mm] <i>For other installation or wall settings see instruction manual</i>	rear	0
	sides	750
	ceiling	500
	Front	1200
	Floor	0
Risk of burning fuel falling out	Pass	
OGC (mg/Nm ³ rel. 13 Vol-% O ₂)	45	
CO-emission of combustion products	0,092 % / 1150 mg/Nm ³	
NO _x (mg/Nm ³ rel. 13 Vol-% O ₂)	81	
Dust mg/Nm ³ at (rel. 13 Vol-% O ₂)	5	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum operating pressure	- bar	
Flue gas temperature T at nominal heat output	243 °C	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	7 kW	
Room heating output	7 kW	
Water heating output	- kW	
Energy efficiency ¹⁷	80 %	
Seasonal Efficiency $\eta_{S,on}$	72 %	

- 9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:

Erich Hänni, Geschäftsführer

Place Cham, Schweiz

Date 10-01-2022

Signature