

18

Product ID:  
2575DM29341

C11

C31

C91

Produced at: RAIS A/S, Industrivej 20, 9900 Frederikshavn, Danmark

- Q-Tee II Gas  
 Q-Tee II C Gas

This appliance must be installed in accordance with the rules in force, and only used in a sufficiently ventilated space. Consult instructions before installation and use of this appliance. Tested and Certified for use on Biopropane.

Efficiency class 1

Production number. \_\_\_\_\_ Burner ID. \_\_\_\_\_

GAS CATEGORY and SUPPLY PRESSURE		HEAT INPUT (Gross, KW)	BURNER PRESSURE (Hot, mbar)	COUNTRY of DESTINATION	
N A T U R A L  <input type="checkbox"/>	I2H	G20 @ 20 mbar	9,1	13,2	AT, BG, CH, CZ, DK, EE, ES, FI, GB, GR, HR, IE, IT, LT, LV, NO, PT, RO, SE, SI, SK, TR
	I2E	G20 @ 20 mbar	9,1	13,2	DE, LU, PL, RO
	I2E+	G20↔G25 @ 20↔25 mbar	9.1/8.4	13.2/16.4	BE, FR
	I2ELL	G25 @ 20 mbar	7,5	13.4	DE
	I2L I2EK I2 (43.46 -45.3 MJ/m3 (0°C))	G20/G25.3 @ 25 mbar	8,5	16.6	NL
CITY GAS <input type="checkbox"/>	I1e	G150.1 @ 8 mbar	9,4	3.5	DK, SE
L P G  <input type="checkbox"/>	I3+	G30↔G31 @ 28↔37 mbar	8	27/36	BE, CH, CY, CZ, ES, FR, GB, GR, IE, IT, LT, PT, SI, SK, TR
	I3P(30)	G31 @ 30 mbar	7	28	FI, NL, RO
	I3P(37)	G31 @ 37 mbar	8	36	BE, CH, CZ, ES, FR, GB, GR, HR, IE, IT, LT, NL, PL, PT, SL, SK, TR
	I3P(50)	G31 @ 50 mbar	8	36	AT, CH, CZ, DE, NL, SK
	I3B/P(30)	G30↔G31 @ 30 mbar	8	27	BE, BG, CY, DK, EE, FI, FR, GB, GR, HR, HU, IT, LT, MT, NL, NO, RO, SE, SI, SK, TR
I3B/P(50)	G30↔G31 @ 50 mbar	8	36	AT, CH, CZ, DE, FR, SK	

Hergestellt für /Produced for:

ATTIKA FEUER AG, Brunnmatt 16, CH-6330 Cham / RAIS A/S, Industrivej 20, DK-9900 Frederikshavn

CE Label: 07-07-2021

Q-Tee II Gas

Q-Tee II C Gas