

| | | | | | | | | | _ |
|---------------------|---|---|---|--|--|--|--|--|--|
| MODEL | F6 2320 | F6 2520 | F6 2720 | F6 2920 | F6 3120 | F6 3320 | F6 3520 | F6 3720 | F6 3920 |
| Size in mm | Topplate: L: 2320mm D: 215mm | Topplate: L: 2520mm D: 215mm | Topplate: L: 2720mm D: 215mm | Topplate: L: 2920mm D: 215mm | Topplate: L: 3120mm D: 215mm | Topplate: L: 3320mm D: 215mm | Topplate: L: 3520mm D: 215mm | Topplate: L: 3720mm D: 215mm | Topplate: L: 3920mm D: 215mm |
| | Bottom box: L: 600mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 700mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 900mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 1300mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 1300mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 1500mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 1700mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 1900mm H: 160mm incl. topplate D: 190mm | Bottom box: L: 1900mm H: 160mm incl. topplate D: 190mm |
| Flame tray size, mm | 2100 | 2300 | 2500 | 2700 | 2900 | 3100 | 3300 | 3500 | 3700 |
| Capacity, liters | 15L | 16.4L | 17.7L | 19L | 20.3L | 21.6 | 23L | 24.3L | 25.6L |
| Burning time, hours | 6.5 - 18.5 | 6.5 - 17.5 | 6.5 - 17.5 | 6.5 - 17.5 | 6.5 - 17.5 | 6.5 - 17.0 | 6.5 - 17.0 | 6.5 - 17.0 | 6.5 - 17.0 |
| Heat output, kWh | 4.9 - 13.4 | 5.3 - 14.7 | 5.8 - 16.0 | 6.3 - 17.2 | 6.7 - 18.5 | 7.2 - 19.4 | 7.7 - 21.1 | 8.1 - 23.3 | 8.6 - 23.6 |
| Net weight, kg | 33 | 35 | 37 | 39 | 41 | 43 | 45 | 47 | 49 |
| Min. room size, m² | 96 | 105 | 14 | 123 | 132 | 141 | 150 | 160 | 169 |

GENEREL INFORMATION

| Produced in | Denmark | | | | |
|------------------|--|--|--|--|--|
| Flame levels | 5 flamelevels + ECO Wave | | | | |
| Sensors | Temperature/Fuel Level/Spillage | | | | |
| Powersupply | 230 V | | | | |
| Fuel Type | Bioethanol 95 - 96.5 % | | | | |
| Flue | Not required | | | | |
| No internal pump | No noice, reduced maintenance, increased reliability | | | | |
| Finish | Black powder-coating | | | | |
| Finish top-plate | 2mm black powder-coated steel | | | | |
| Glass | Tempered glass, T6mm H70mm The glass is placed in customised glassholders | | | | |
| Application | Indoor use only | | | | |

Decoflame's Denver F6 bio-burner ranges from 620 mm to 3920 mm in length. Developed and manufactured locally, these burners offer exceptional flexibility for any project size. The Denver F6, designed by Decoflame's expert engineers, is a groundbreaking innovation in modern fireplaces. Equipped with patented BEV (Burning Ethanol Vapours) technology, it represents the pinnacle of luxurious supplementary heating solutions.

Denver F6 impresses with advanced features, including app control, Bluetooth connectivity, and sophisticated safety systems. Additionally, it offers SmartHome integration and an external automated refuelling tank system, ensuring seamless and efficient operation.


BIOETHANOL


For use and information about bioethanol, please visit: decoflame.com.

Please be aware that bioethanol is essential to a proper use and gurantee of your product.




DENVER F6 CAN BE INSTALLED IN VARIOUS CONSTRUCTION OPTIONS. EG:











Open to front and 1 side (Left or right)

Open to front, back and 1 side (Left or right)





Single standing

Open to front and 2 sides